



Klemsan®

604623 ANC-8(220VAC/DC)

Alarm Annunciator

Voltage	AC	220V
	DC	220V
Input Signal	Frequency	45-65Hz
	Numbers	8
	Response Time	25±10ms
Output Contacts	Type of Output	Relay
	Number of Contacts	2
	Type	1 NO (SPST)
	Max. Ratings - AC	5A/277V;1385VA
	Max. Ratings - DC	5A/30VDC;150W
	Mechanical Lifetime	≥10 ⁸ operation
	Electrical Lifetime Operations (for NO Side)	1x10 ⁵ (5A@250VAC)
Window	Numbers	8
	Colours	Red / Green selectable
	Size	30.5 x 15.5
	Illumination	With 4 pcs. red leds or 4 pcs. green led
Flash Rate	Slow	60 Flash / Min.
	Fast	180 Flash / Min.
Window	Legends	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.
General	Time Range	0,2,5,10,15,20,25,30 adjustable
	Built-in Push Buttons	4 (Hom, Ack, Delete, Test)
	Buzzer	✓
	Real Time Event Recording	6080 logs

	Battery Life	> 5 years
	Protection Class	IP50 (front) IP20 (back)
	Connections	Screw terminal
	Weight (g)	280
	Packing Unit	1
	Schematics	—
	Drawings	—
Communication	Protocol	Modbus RTU
	Baud Rate	1200-57600
	Isolation	2500Vrms
Supply	Frequency	45-65Hz
Power Consumption	DC	<3W
	AC	<5VA
Ambient Conditions	Operating Temperature	-20°C +70°C
	Storing Temperature	-30°C +80°C
	Relative Humidity (No Condensation)	Maks. 90%
Bezel/Overall	Height	96.8
	Width	96.8
Panel Cutout	Height	89,6
	Width	89,6
	Depth	65
EMC-EMI	61000-6-2, 61000-6-4	✓

Avrupa standartlarına uygunluk belgesi - CE Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Türk Standartlarına Uygunluk Belgesi - TSE Certificate

Anc 8 - 16 Setup

ANC User Guide

Aydinger

Order Info

604623 Alarm Annunciator

© 2023 Klemsan A.Ş.
www.klemsan.com